



Energy Saving		CO <sub>2</sub> Tailpipe Emission Elimination	
K9	One K9 Saving 128,428 USD in 5 and a quarter Years		Diesel Bus
130 kWh <sup>©</sup>	Energy Consumption / 100 km		40L
0.13/kWh	Energy Price (USD)		1.25/L
16.9	Cost/100 km		50
388,000	Highest Mileage (km)®		388,000
65,572	Total Cost (USD)		194,000
The data collected was based	on the highest single mileage	of the K9 bus in Shenzhen	from January 2011 to March 2017.

① Due to changes in road conditions and driving habits, the actual date may be different with ECE data.

② The above operational information collected from ShenZhen real data Jan. 2011 - Mar. 2017.

Note: Calculation Based on Shenzhen Energy Price.

## Safety

Intelligent Battery Management System (iBMS) assists with balancing and charging safety, helping produce the safest battery on the road.

### Eco

Produce ZERO emissions, eliminates the need for particulate traps, and makes oil changes and other polluting consumables a thing of the past.

## \$aving

Energy consumption amounts 1.3 kWh/km (assuming 0.18 USD/km) while eliminating usual service costs associated with diesel, CNG and hybrid alternatives.

### Longevity

Battery life is above 4,000 cycles; no need for battery replacement under normal use.

### Comfort

A quiet ride with zero emission is an ideal choice for rejuvenating energy along the road of green journey.

### Longest Range

The industry leading driving range 250+ kilometers per charge.

### **K9 SPECS**

Dimensions			
Length/Width/Height	12,000 mm / 2,500 mm / 3,400 mm		
Wheelbase	6,100 mm		
Curb Weight	13,100 kg		
Gross Weight	18,000 kg		
Seats	Up to 35		
Wheelchair Area	1		
Performance			
Top Speed	70 km / h	70 km / h	
Max Gradeability	≥20%	≥15%	
Min Ground Clearance	140 mm	140 mm	
Range①	≥250 km	≥250 km	
Turning Radius	≤12m	≤12m	
Approach / Departure Angle	7.5°/7.5°	7.5°/7.5°	
Chassis			
Suspension	Air Suspension (ECAS system)		
Brakes	Front & Rear disc, ABS, Regenerative Braking		
Tires	275/70R 22.5		
Motor			
Motor Type	AC Synchronous Motor		
Max. Power	300 kW (150 kW×2)	180 kW (90 kW×2)	
Max. Torque	1,100 Nm (550 Nm×2)	800 Nm (400 Nm×2)	
Battery			
Battery Type	BYD Iron-Phosphate Battery		
Battery Capacity 2	324 kWh		
Charging			
AC Charging	80 kW (40 kW×2)		
Charging Time ③	4-5 h		


The above specifications are for the standard vehicle. It is subject to regional needs and regulations. Specs updated: June 2017.

- ① Test standard GB/T 19754: actual range will vary depending upon driving/charging habits, speed, conditions, weather, temperature, and battery age.
- ② The battery capacity is initial capacity. It will decrease with time and use.
- 3 The battery age and outside ambient temperature both play a role in charging times.











## **Reliable-Business Case Example**

Shenzhen Case

The Earliest All-Electric Bus Fleet

➤ Started: Jan. 2011

Fleet: 780 Electric Buses

Total Mileage: Over 154 Million km

Single Mileage: Over 388,000 km

Battery: Long Cycle Life (Above 4,000 cycles)

As of Mar, 2017

## **World-Leading Technologies**

▶ Being one of the leading rechargeable battery manufacturers in the global arena, BYD is the only organization that majors in battery, electric motor and electronic control system.


of lost braking energy and you g

# BYD ELECTRIC **VEHICLE CHARGING** SOLUTIONS

BYD charging points are small and easy to fit. As they don't require a special station, they can be easily placed anywhere a vehicle would be parked, such as home, work, shopping centres and public car parks.







BYD AC Charging Adapter			
Charging Mode	AC Charging		
Input voltage	Three phase AC 380 V / 400 V		
Input current	≤126 A		
Intput power	≤80 kW		
Physics			
Length/width/height	690 mm/400 mm/200 mm		
Net weight	30 kg		
Length of the cable	3 m		
Install form	Wall-mounted		
Safety			
Protect function	Short circuit protection/Over-temperature protection/ Lightning protection		
Housing protection level	IP55		

## BYD ELECTRIC BUS GLOBAL FOOTPRINTS









## BYD Electric Bus on the Road-Exciting Moments









